



Advanced Scroll Technology Solutions for Medical OEMs

TECHNICAL DATASHEET

P05H012A-BLDC

07.21.2026 Rev. 00

Introducing **Silent Series™ Scroll Compressors** from Air Squared – Ultra Quiet, Compact, and Engineered Specifically for Medical OEMs



100% OIL-FREE

Maintain the purity of your system with 100% oil-free scroll technology



ULTRA-QUIET, SMOOTH OPERATION

Best-in-class NVH, dynamically balanced, valve-less, and nearly pulsation-free



COMPACT, LIGHTWEIGHT DESIGN

Integrated cooling and BLDC drive provide simple installation and minimal footprint



DURABLE, ROBUST SOLUTION

Engineered to exceed the life and reliability of diaphragm and piston technology



EFFICIENT PERFORMANCE

Continuous compression process with no throttling or re-expansion losses



BLDC CONTROL

Proportional speed control delivers ideal performance over a range of duty cycles – 100% continuous to intermittent

OPTIONS AND ACCESSORIES

BLDC Demo Controller (External, Wired)
Inline Discharge Filter (Recommended)
Check Valve (Recommended)
Mounting Bracket

OEM CUSTOMIZATION

Custom Mounting and Fan Location
Custom Electrical Connectors
Custom Port Fittings

Qualified OEMs should consult Air Squared for custom configurations and application-specific requirements.

Contact sales@airsquared.com.



Specifications


PRESSURE	RATED	2 bar _g	
VOLUME RATIO		2.75	
FLOW	RATED	5.5 lpm _v	
DISPLACEMENT		2.55 cm ³ / Rev.	
SOUND LEVEL		25 dB(A)	Average at Nominal Operation
NET WEIGHT		0.46 kg	
AMBIENT TEMP. RANGE	MIN.	-40 °C	
	MAX.	40 °C	
COOLING		Attached Fan	
PORTS		10-32 UNF	Inlet and Outlet
MEDIA		Air	
REGULATORY		RoHS, REACH, Other	
PART NUMBER		P05H012A-B01	

Electrical


MOTOR		0-12 V Brushless DC	Hall Sensors, 233 Rev./V
SPEED	RATED	2,800 RPM	at 12 V
CURRENT		1.5 A	at 1,500 RPM
		2.3 A	at 2,800 RPM
CONTROLLER	DEMO	External, Wired	Analog, PWM, Other
	NONE	Customer-Supplied	
FAN		12 VDC	

Performance

FLOW CHARACTERISTICS




POWER CHARACTERISTICS



Flow Characteristics reflect nominal volume flow at NIST standard inlet conditions. Power Characteristics reflect nominal electric power consumption in Thornton, CO USA with standard motor and controller losses.

Dimensions



Dimensions in millimeters unless otherwise stated.

©2026 Air Squared Group, LLC All rights reserved.

This document is subject to copyright and other intellectual property rights of Air Squared Group, LLC and its affiliates. This material may not be modified, reproduced, or copied, in whole or in part, without the prior written permission of Air Squared Group, Inc., its affiliates, or its licensors.

Technical information is believed to be accurate and reliable. Performance specifications are based on testing of nominal units at Air Squared. Air Squared Group, LLC and its affiliates do not warrant, guarantee, or assume liability in connection with information provided herein. All information is for reference use only - visit <http://airsquared.com> for current specifications.

Customer-specific requirements and application conditions may adversely affect performance and product life. It is the responsibility of the user to determine the suitability of the product for its intended use.



Learn More About Oil-Free Scroll Technology at
<http://airsquared.com>

